




Semi-Automatic Tape Sealer  
Up to 30 cases per minute




**RSC Case**  
The BEL 150X  
seals RSC  
cases.

## Over-size Semi-Automatic Case Taper



### Squareness Assured

BEL's innovative and powerful Uni-Drive system synchronizes conveyor belt speed, eliminating case skew, so that cases leave the machine squarely taped.



### Lasting Performance

The BEL 150X features heavy duty, corrosion resistant aluminum C-Beam construction and compact design to provide lasting performance in the most demanding production environments.



### Superior Tape Application

The BEL 150X is equipped with state-of-the-art DEKKA High Performance stainless steel tape heads that are easily loaded in or out of the machine in 30 seconds or less.



### Easy Case Change

The BEL 150X is user-friendly, enabling the operator to make box size changes from either side of the machine quickly and easily, in 30 seconds or less.

BEL 150X Case Sealer

# BEL 150X Over-size Semi-Automatic Case Taper

## BEL 150X Features

- Paint free, corrosion resistant frame, guards against contamination from flaking or peeling paint
- Built-in safety systems that protect against power interruption or overload
- Uni-Drive squaring mechanism that mean more presentable cases
- Quick and easy maintenance, meaning a minimum of downtime
- Standard DEKKA 22 Stainless Steel 2" tape heads and optional DEKKA 3" tape heads available

## Complete Solution



### BEL 505 Case Former

The BEL 505 improves efficiency and ergonomics. Inserting a case into the BEL 505 results in all four bottom flaps being automatically folded, leaving hands free to pack.



### BEL 150X Oversize Case Taper


The oversize model is available to accommodate larger case requirements.



### BEL 150SS Stainless Steel Case Taper

The stainless steel is available for washdown environments.

## How the BEL 150X Works



**RSC Case**  
The BEL 150X seals RSC cases.



### 1 Quick Change Handle

Upper assembly is adjusted with a hand wheel which increases or reduces size in seconds.



### 2 Uni-Drive Case Transport

Uni-drive system synchronizes the case conveyor, assuring case squareness during taping.



### 3 Top & Bottom Sealed

Superior case sealing performance is achieved with its quality tape application. The BEL 150X comes standard with DEKKA tape heads.

## BEL 150X Specifications

Case Size Range	Length	Width	Height
Minimum	8" 203 mm	6 1/2" 165 mm	5" 127 mm
Maximum	unlimited	25 1/2" 648 mm	30" 762 mm
<b>Infeed/Outfeed Height</b> (with adjustable foot pads) Note: Castors add 6" to minimum and maximum height.			
Minimum	19 1/2" (495 mm)		
Maximum	28" (711 mm)		
Machine Speed: Up to 30 cases per minute			

\* Specifications are subject to change without notice.



Your Local Distributor:  
Marsh Micro Systems, Inc.  
1084 Duncan Ave.  
Chattanooga, TN 37404

Phone: 423-629-6245  
Fax: 423-624-7019  
Email: sales@marshmicrosystems.com  
Web: www.marshmicrosystems.com

a division of Pro Mach 

Backed by Wexxar's warranty and experienced, nationwide service team.