

AVAILABLE OPTIONS ON AUTOMATIC MODELS

WHY COMPROMISE? CUSTOMIZE!

Customizing a stretch wrapper can make all the difference between boosting productivity and maximizing it. Our affordable options make it easy for you to tailor your stretch wrappers to meet your specific applications. Enjoy a level of performance other machines cannot match. Following are the main options we offer on our automatic stretch wrappers. For additional information and pricing, please contact Marsh Micro Systems (423) 629-6245, sales@marshmicrosystems.com. Here are the most popular options:

CARRIAGE

- 10" film roll carriage adapter
- Adapter bracket to use 20" film on 30" carriage
- 30" NO-THREAD[®] powered pre-stretch carriage
- Sprocket Counter
- Low film alarm
- Pneumatic roping single/dual

CONDUITS

- Rigid steel conduit

CONTROLS

- Allen Bradley 5/05 PLC
- Allen Bradley 5/04 PLC
- Allen Bradley PanelView 1000 Plus
- Communication link I/O
- Remote lanyard start/stop
- Remote pull cord start/stop
- Remote pedestal start/stop
- Modem

CONVEYORS

GRAVITY

- 5' gravity roller conveyor
- 10' gravity roller conveyor
- 15' gravity roller conveyor
- Gravity roller conveyor transition set - 2 x 6" contour sections

PASS HEIGHT

- Standard pass height on all models is 18"
- Minimum pass height on WCA models is 16"
- Minimum pass height on WCRT models is 12"
- 18" to 24" pass height
- 24" to 36" pass height
- 36" to 45" pass height

POP-UP

- Pop-up process conveyor
- Pop-up for turntable conveyor
- 6,000 lbs capacity pop-up
- Pop-up rotator

POWERED

- Powered belt conveyor
- 2 chains powered conveyor
- 3 chains powered conveyor
- Conveyor drive package
- Conveyor contour end roller
- Conveyor powered roller turntable pneumatic or electric 90° index
- Powered roller conveyor
- Powered roller single contour conveyor
- Powered roller double contour conveyor
- Elevating powered roller conveyor
- Elevating pallet jack powered roller conveyor (end or side access)
- 2 chain lateral transfer powered conveyor
- 3 chain lateral transfer powered conveyor
- 3 chain bi-lateral transfer powered conveyor
- BFR 42" conveyor
- BFR 48" conveyor
- BFR 60" conveyor
- BFR 64" conveyor
- Load alignment guides
- 5,000 lbs or 6,000 lbs capacity
- Larger roller diameter
- Credit removing 11.5' process conveyor – WCRT models
- Credit removing 2 x 5' I/O conveyor – WCA models

SPEED

- Conveyor speeds above 30 fpm
- Conveyor twin speed package

UP-ENDER

- Hydraulic up-ender conveyor

DOCUMENTATION

- Installation operation manuals sets
- PLC program print out
- Manual on CD

HEAT SEAL

- Conveyor side mounted heat seal
- Floor mounted heat seal
- Wipe arm mounted heat seal

ENCLOSURE

- Enclosure 6" or 12" leg set
- Sloped top on enclosure
- Fluorescent light in control panel
- Main disconnect switch AB flange mount
- NEMA 4x stainless steel enclosure
- Change WCA tower to NEMA 4/12 enclosure

FILM CLAMP

- Hydraulic elevating film clamp
- Clipper/cutter for netting
- Knotter
- Automatic compact clamp

MOTORS

- Wash down motor
- Harsh environment motors
- Inverter duty motors

PAINT

- Custom color (using our regular paint supplier)
- Epoxy
- Steel-it

PHOTOEYES

- Background suppression autoheight photoeye for dark or shiny loads
- AB 9000 photoeye
- Forklift detection photoeye

SAFETY

- Safety warning buzzer
- Safety E-stop station
- Safety fencing
- Safety gates infeed/outfeed
- Safety illuminated E-stop
- Safety light curtain
- Surge protector

SCALES

- Conveyor mounted load cells
- Sub conveyor plate mounted load cells

SLIP SHEET

- Slip sheet applicator
- 4 sides bottom slip sheet tab up-folder
- 2 sides bottom slip sheet tab up-folder

SPEED

- 22 RPM on turntable (WCA-200 only)
- 24, 30 or 35 RPM on rotary arm (WCRT-200 only)
- Dual speed for unstable loads

TEMPERATURE

- Cold package "A" (41° to 32°F)
- Cold package "B" (32° to 5°F)
- Cold Package "C" (5°F to -31°F)
- Warm package "A" - Vortex (up to 115°F)
- Warm package "B" - Air Conditioning (104°F to 140°F)
- Fan and exhaust (100°F to 104°F)

TOP PLATEN

- Electric tower side mounted top platen
- Electric arm 2nd boom mounted top platen
- Pneumatic top platen for rotary arm machine
- Top platen with 4 sides tab fold down

TOP SHEET

- In-cycle top sheet dispenser
- In-line top sheet dispenser to straddle Wulftec conveyor
- In-line top sheet dispenser to straddle customer's conveyor
- Static eliminator for in-line top sheet dispenser
- Increased top sheet roll capacity range 72" to 84"

TRANSFORMERS

- Transformer 60HZ
- Transformer 50HZ
- Epoxy coated transformer

WRAP DIAMETER EXTENSION

- 1' extension
- 2' extension
- 3' extension

WRAP HEIGHT EXTENSION

- 1' extension
- 2' extension
- 3' extension

MISCELLANEOUS

- 90° index feature on exit or infeed
- Forklift safety bumper on conveyor
- Forklift stopper (floor mounted)
- Air compressor
- Electric air dump valve